

FLEXO PRINTING SLEEVES & BRIDGES



WWW.TECH-SLEEVES.COM





WORLDWIDE FLEXO SLEEVE SOLUTIONS



At Tech Sleeves, we constantly improve our products to enhance the overall performance and quality of our sleeves and bridges. We provide high-quality products with reliable delivery t mes.

We develop and use new technologies on our sleeves and bridges to become global leaders in this feld.









1 - Base Layer

- Expandable strong innercore without cracking. It prevents slipping on the mandrel
- This inner core is 100% moisture, UV light and chemical resistant.

2 - Compressible Layer

- This layer enables the sleeve to expand and retract for a smooth f t onto the cylinder or bridge.
- Due to the edges of our sleeves being completely sealed, this layer is always fully protected.

3 - Tech Core Light Layer

- Lightweight core material designed to limit bounce and maximize the durability of the sleeve.
- Allows sleeve build-ups to all wall thicknesses and of ers the lightest sleeves on the market.

4 - UV-cured Vinyl Ester resin outer layer

- Guaranteed 82 Shore D outer layer hardness, which is signif cantly higher than market standard.
- This outer layer of ers an extremely st f, long-last ng frm sleeve with excellent tape adhesion propert es.

LIGHTWEIGHT

TECHNOLOGY

Tech Sleeves® manufactures light weight composite sleeves and bridges for the global f exographic print ng industry. By using the highest quality grade of materials, Tech Sleeves® is able to outperform any sleeve on the market in terms of durability, consistency and dimensional accuracy.

Tech Sleeves® and Tech Bridges® are qualified for high printing speeds of up to 800 m/min, or 2,624 f /min and within the industry they are recognised as one of the lightest, st f est and stable sleeve and bridges on the market with weight savings of up to 40%.

ADVANTAGES OF OUR SLEEVES & BRIDGES




SLEEVE OPTIONS




RUBBER SEALED EDGES WITH REINFORCED SLOT

Increases the lifetime of a sleeve by making the end of the sleeve resistant to impact. Prevents damages to the positioning pins in the press and mounting machines without weakening the registration slot.



SMART SLEEVE (RFID CHIP & MAGNET)

RFID embedded sleeve which allows reading and writing for the purpose of identification. Works with the new and our existing systems. It improves the printing process and prevents mistakes from using the wrong sleeves in the press.



CONDUCTIVE SLEEVE

All the sleeves from Tech
Sleeves can become conductive
sleeves with the use of carbon.
Conductive sleeves conduct
electrostatic charges, which can
occur in the printing area and go
into the grounded printing press.
Many companies choose this type
of sleeves for printing.

CONFIGURATIONS

FEATURE	ADVANTAGE	TECH LIGHT®	TECH PRO LIGHT®
Axial zero line	Helps in defining the zero position	•	•
Milled slot	A durable slot solut on	•	0
Sealed edges	Ensures chemical and moisture protect on providing dimensional stability	•	•
Rubber edges	Provides maximum durability		•
Metal Reinforced Slot	Great notch durability, bonded in the rubber for maximum durability so not possible to come loose		•


"O": Optional





CASE STUDY:


FORCE VS. DEFLECTION



Tech Sleeves uses high-quality materials with a researched build-up formula that maximizes the robustness of the sleeve.

Based on a recent defect on study, **Tech Sleeves** proved to have significantly less defect on compared to the industry leading compet tors. The graph above shows that the sleeves from Tech Sleeves need almost twice the force required to achieve the same level of defect on.





BRIDGES/ADAPTERS

The **Tech Bridge** is one of the **most advanced bridge/adapter** in the market. It is made using the same strong materials as the Tech Sleeve, and it is available in either Separate Air or Air-Through. This bridge is **extremely durable** and resistant to chemicals, heat and the stresses faced in a print ng press.

One of the biggest advantage of the Tech Bridge, is that it comes standard with an **outer metal ring on both sides**. It protects the bridge and prevents end damage.








BRIDGE VERSIONS



SEPARATE AIR

A Separate-Air bridge works using a separate air source that is not the mounting mandrel. The operator can choose which source of air to turn on and load the sleeve or the bridge separately.



AIR THROUGH

The Air-Through bridge works by directly providing air via the mandrel. The bridge has air vents that can be lined up with the mandrel and allow the required air to flow. It is used in cases where the wall thickness of the adapter is guite thin.



SOFT COATED


The Soft Coated Tech Bridges are used to carry flexible, thin sleeves (seamless sleeves) which are available in densities of 40, 50 and 60 ShA. They can be Separate air connection or airthrough.





Spacer

(Only applicable to hard bridges) Provides the possibility to use sleeves of different widths on one bridge. The spacer sleeve provides a registration pin to align all sleeves on the operator side.



Miller Valves

(Only applicable to Hard Separate air bridges) Control the air flow of the bridge by covering the air holes with valves. Direct the air flow to where required therefor creates flexibility to use multiple sleeve width on one bridge with alignment on the drive side.

TECHNICAL SPECIFICATIONS



CATEGORY	SPECIFICATIONS
Tolerance	Tech sleeves® are guaranteed to have a tolerance on diameter of +/- 0.020 Mm / < 0.001 Inches.
Precision grinding	TIR < 0,020mm/ 0,001 inches, measured on a carrier/cylinder with a TIR 0,005mm/ 0,0002 inches.
Outer surface	Smooth with polished fnish



Repeat length	240-1500 Mm / 9,449 - 59,055 inches.
Register line	Standard 1x zero axial line included. Addit onal axial and/or radial lines on request.
Register slot	As ordered by the customer.



Mounting	On air cylinders/ carriers with minimum air-pressure of 6,5 bar and an air-f ow of 12 liter/second
Wall thickness	0.9 - 110 Mm (thicker upon request) / 0,035 - 4,330 inches.
Sleeve length	Max. Length of 2100 mm / 82,677 inches.



Temperature	Tech Sleeves® and Tech Bridges® have a maximum operating temperature of 80 degrees Celsius (176 degrees Fahrenheit)
Chemical resistance	Resistant against all solvents used in the f exographic industry for plate cleaning.
Cleaning advice	Clean with ethyl alcohol mixed with maximum 15% ethyl acetate.
Label	The dimensional specifications are shown on the label inside the Tech Sleeves®.

TECH SLEEVES GLOBAL

SALES, SUPPORT & SERVICE





GLOBAL SALES & SUPPORT

Tech Sleeves has a global team of 20 sales and support professionals available in all working hours worldwide.



LARGE AGENT NETWORK


With more than 50 agents worldwide, Tech Sleeves ensures local sales and support in your native language.



EXCEPTIONAL KNOWLEDGE

Leveraging 30 years of experience in the flexo industry, Tech Sleeves has supreme knowledge in all aspects of flexo printing.

ONLINE SUPPORT SYSTEM



Are you having an issue?

You can easily create a ticket online at: www.tech-sleeves.com

Our experts will get in touch with you with a solution in a short time.

You can also find useful information regarding the use and maintainance of your sleeves. For more inforamation, scan the QR code below.





SLEEVE STORAGE SYSTEM



Our customized Sleeve storage system has been co-developed with AV Flexologic for workspace opt mizat on in the press, while providing opt mal protect on for your sleeves.

BENEFITS

- Custom Engineered
- Sturdy modular design
- Made from tubular steel
- Organized way of storage
- Prevents sleeve damage and swelling





Pins for holding the sleeves in place



Vertical sleeve storage to prevent sleeve swelling

TIR SLEEVE MEASUREMENT SYSTEM



The TIR measurement system is the winner of the International print & innovation award 2015. It is analyses the quality of the sleeve or cylinder by measuring the '3D landscape' of the surface.

A high quality laser takes the measurement with an accuracy of 5 micron. This informat on provides a thorough insight on its condition. Subsequently, it can be placed with right pre-set ings in the press to prevent press downtime. It calibrates any irregularities to ensure precision on micron level. A full report is generated to keep track of any irregularities. TIR also stores records for future reference.

ADVANTAGES


- Reduct on in press downt me due to worn out print ng sleeves which end up in the f exographic print ng press
- Quick and easy usage
- Allows bet er control over the print ng process
- Ident fy out-of-spec sleeves
- Stores the measurement report

OPTIONS

Pressure roller for safe tape application without air bubbles

Cut ng knife with an adjustable depth to prevent sleeve damage while cut ng tape

Tape holder for easy tape applicat on




DEMOUNTER



The Demounter is a machine mainly designed to prevent damaging the print ng plates and sleeves. It ef ciently removes the print ng plates and mount ng tape from sleeves, **without any damage.**

A motor driven silicon roller generates frict on to pull the print ng plates or mount ng tape of the sleeve or cylinder. It distributes equal force across the width, as opposed to edges, to **demount the plates safely.** Along with saving plates, it also saves t me to allow the operator to focus on other act vit es in the prepress department.

ADVANTAGES Reduces costs due to damaged plates Quick return on investment Saves t me in prepress department Easy to use and minimal force required OPTIONS Pneumat c cones for applying tape Cut ng knife





Optional cones for tape application

TECH CART



The Tech Cart is a sleeve carriage or a sleeve cart, specifically designed to eliminate discomfort. By holding the sleeves horizontally, it ensures that you can load and unload the sleeves **without any extra physical effort**. With the 360 rotating wheels and cart handle, you can easily manoeuvre the cart around.

Along with convenience, Tech Cart® also ensures **safety** for the sleeves. The tubular steel structure makes the cart extremely sturdy. Moreover, Tech Cart® can be customized to hold the number of sleeves you need and suit the sleeve sizes as per your requirement. Tech Cart® is thus the ult mate way to transport your sleeves.

FEATURES

- Customized engineering
- Ergonomically designed
- Sturdy tubular steel structure
- Rubber end rings
- 360 rotating wheels
- · Cart handle

BENEFITS

- Easy transportat on of sleeves
- · Easy loading/unloading
- · No physical heavy lif ing
- No damages to sleeves durin transportat on





REQUEST A QUOTATION:

Info@tech-sleeves.com

Contact us:

Tel.:+31 17 25 03 611

Fax. :+31 17 24 37 919

H. Kamerlingh Onnesweg 2 2408 AW Alphen a/d Rijn The Netherlands